

*The second step in a two step cleaning system. It is used after applying KOLD KLEEN I as the first step cleaner. Removes oily soils and helps break the static bond that causes dirt to cling to painted surfaces. Regularly used by cleaning contractors.*



### Where To Use

Truck Fleets      Construction Equipment

### Dilution and Directions

KOLD KLEEN I and KOLD KLEEN II should never be mixed together in the same container. This product is ready to use through the pressure washer at 1/25, with cold water. Avoid applying on windy days. It is generally recommended to wash from the bottom up and to test surfaces for suitability before washing. Begin by washing vehicle, equipment or surface to be cleaned with properly diluted Kold Kleen I. Pressure rinse with cold water immediately. Apply Kold Kleen II immediately following Kold Kleen I.

### Technical Specifications

COLOR: ..... Transparent Red	VISCOSITY: ..... Water Thin
FORM: ..... Liquid	STORAGE(Unopened):..1 Year @R.T.
SCENT: ..... Odorless	BIODEGRADABLE: ... Yes
pH: ..... 14.0	WEIGHT/GAL: .....8.6 lbs.
FLASH POINT: None	SHIPPING CLASS: .....8, Packing Gr III
FOAM: ..... Low/Medium	PACKAGING: .....5 gal, 55 gal
TYPE: ..... Sodium Hydroxide 2nd Step Truck Wash	

