

A high quality product that maintains the "wet look - no skid" finish on floors. Used routinely for low speed and high speed floor maintenance between strippings.



Where To Use

Vinyl Tile	Linoleum	Sealed Wood
Stone	Rubber	Asbestos Tile
Concrete	Asphalt Tile	Terrazzo

Dilution

As is.

Directions

Sweep dirt from floor and remove obvious soil buildup. Wash with neutral detergent such as SUN SHINE NEUTRAL CLEANER or AP-7 and let dry completely. Spray MAINTAIN in 3 to 4 foot wide sections in front of machine and buff to a high shine paying close attention to heavy scuff marks. One gallon covers approximately 2000 square feet.

Technical Specifications

COLOR:	Milk-white	TYPE:	Acrylic Polymer
FORM:	Liquid	SOLID CONTENT:	6%
SCENT:	Mild Solvent/Polymer	INITIAL GLOSS:	Excellent
pH:	8.0	RECOAT DRYING TIME:	N/A
FLASH POINT:	None	COVERAGE:	2000 - 2500 sq ft
FOAM:	None	LEVELING:	Excellent
VISCOSITY:	Water Thin	SLIP COEFFICIENT:	0.5
STORAGE(Unopened): .	1 Year @R.T.	REMOVABILITY:	Excellent
BIODEGRADABLE:	Yes	SCUFF RESISTANCE:	Excellent
WEIGHT/GAL:	8.4 lbs.	DETERGENT RESISTANT:	Excellent
SHIPPING CLASS:	None		
PACKAGING:	12x32, 4x1, 5 gal		

