

A highly versatile, high solid, extended wear metal cross linked floor sealer/finish. Formulated with exclusive micro molecular technology for easy maintenance, high gloss, exceptional film clarity and outstanding "off the mop gloss".



Where To Use

Vinyl Tile	Linoleum	Sealed Wood
Terrazzo	Rubber	Asbestos Tile
Asphalt Tile	Concrete	

Dilution

As is.



Directions

Prior to application, floor should be completely stripped of all old finish, scrubbed or cleaned. Follow stripping procedure from the online Simoniz floor care training video. The floor should be completely dry before applying first coat and all subsequent coats. Apply in thin coats, evenly. If floor is old or in poor condition, two coats of Simoniz® Super Sealer are recommended. Then apply finish. On unsealed floors, apply 4-5 coats. On cleaned or scrubbed floors, apply as needed. Be sure to use a different mop for stripping, sealing and finish. Allow 24 hours for curing before burnishing.

Technical Specifications

COLOR:Milk-white	FORM:Liquid
INITIAL GLOSS:High	SCENT:Mild Solvent/Polymer
RECOAT DRYING TIME:.....<30 Minutes	pH: 8.0
COVERAGE:2500 - 3000 sq. ft.	FLASH POINT: None
LEVELING:Excellent	FOAM:None
SLIP COEFFICIENT:0.57	VISCOSITY: Water Thin
REMOVABILITY:.....Excellent	STORAGE(Unopened): 2 Year @R.T
SCUFF RESISTANCE:Very Good	BIODEGRADABLE: Yes
DETERGENT RESISTANT:....Very Good	WEIGHT/GAL: 8.5
HIGH SPEED BURNISH:Yes	SHIPPING CLASS:None
PACKAGING:4x1, 5 gal, 55 gal	TYPE:Acrylic Polymer



* FLOOR COATING AND FINISHING MATERIAL AS TO SLIP RESISTANCE ONLY



201 Boston Turnpike, Bolton, CT 06043-7203 800-227-5536 • 860-646-0172 • FAX 860-645-6070

www.simoniz.com www.simonizjanitorial.com

All labels are GHS compliant.